



REFRIGERANT RECOVERY STATION WITH LCD DISPLAY ST-520D

Refrigerant category III	R12, R134a, R401C, R406A, R500, R1234yf
Refrigerant category IV	R22, R401A, R401B, R402B, R407C, R407D, R408A, R409A, R502, R509
Refrigerant category V	R402A, R404A, R407A, R407B, R410A, R507, R32
Oil separator	NO
Power supply	230 V / 50 Hz
Engine power	0.75 kW (1 HP)
Engine speed	2500 rpm
Maximum current consumption	6,0 A
Compressor	piston, oil-free, air-cooled
Automatic switch	38,5 bar / 3850 kPa (558psi)
Fluid recovery efficiency cut. III/IV/V kg/min	2,4/ 2,70/ 3,50
Push/pull recovery efficiency cut. III/IV/V kg/min	7,50/ 8,50/ 9,50
Weight of the complete set	12,1 kg



REFRIGERANT RECOVERY STATION WITH LCD DISPLAY ST- 520D

Working temperature	0°C~40°C / 32~104°F
---------------------	---------------------

Dimensions	345 x 250 x 320 mm
------------	--------------------

Scales	10,5 kg
--------	---------

Hose connection	2 x 1/4" SAE
-----------------	--------------

Included in the set	spare filter, repair kit for control valve
---------------------	--

Packaging	cardboard
-----------	-----------